
TUGS & TOW TRACTORS: Diesel Tow Tractor

Towing Tractor QCF series

- Strong power.
- Modern styling with innovative design elements.
- Ergonomically designed spacious and comfortable cabin.
- Mell-located instrument panel for easy viewing & Conveniently controlled driving system.
- Imported edition binding power and gearing parts realize synchronized or stepless shifting, and provide the excellent performance.
- The dual stages towing hitch operates easily.
- ▲ The whole power steering ensures steady and safe control of the tractor.







	Power type		Diesel		
Model				QCF200	QCF250
Performance	Max. drawbar pull		KN	20	25
	Max. towed weight at dry even concrete surface	With one trailer	Kg	26000	33000
		With a train of trailers		39000	49000
	Max. travel speed	Forward	Km/h	26	
		Backward		23	
	Max. gradeability (without load)		%	38	
Dimensions	Overall length (with coupler) A			3085	
	Overall width B			1440	
	Overall height C			1440	
	Wheelbase D			1600	
	Front overhang 8			640	
	Rear overhang(with coupler)			845	
	Front tread (mm	1230	
	Rear tread			1190	
	Min. turning radius (outer)			3265	
	Floor height J			425	
	Seat height K			980	
	Center height coupler L			350/450	
	Min. ground clearance M			130	
Weight	Truck weight			3550	4050
	Weight distribution	Front axle	Kg	1100	1080
		Rear axle		2450	2970
Tyre	Front tyre			650-10-10PR	
	Rear tyre		700-15-12PR		
Engine	Model			NISSAN TD27	
	Displacement		CC	2663	
	Rated output		Kw/rpm	44.1/2400	
	Rated torque		N·m/rpm	172/1600	

