



# MATERIALS HANDLING | LIFT TABLES

## Tilt Work Table

- ▲ Lift table are designed for use in shipping and receiving rooms, warehouse stock rooms, shops, laboratories, stores, etc.
- ▲ Each unit comes equipped with steel platform, adjusting knob, base frame, 4" polyurethane casters, and all mounting hardware.



TWS150



TWS300



MLT2000

Article No.	TWS150	TWS300	MLT2000-1	MLT2000-2
Type	Tilting Work Stand		Mechanical lift table	
Capacity	kg	70	140	1000
Platform	mm	560x533	610x610	610x914
Raised Height	mm	960	1066	1066
Lowered Height	mm	711	800	610
Fast/Slow		--	Fast/Slow	
Tilt Angle		0-45°	0-30°	--
Caster		4 Swivel casters, 2 with brake		2 Rigid, 2 Swivels with brake
Packing Size	mm	580x580x190	640x650x790	650x960x650
Net Weight	kg	25	39	65

## Mobile Scissor Lift Table

- ▲ Economic range but reliable.
- ▲ New design to meet norm EN1570: 1999.
- ▲ New hydraulic system increases safety and protects your goods, tepless rate of lowering system remains irrespective of the weight of the load.



Foldable Handle



Optional Handle with Plate Protection

Article No.	TF15	TF30	TF50	TF75	TF100	TFD35	TFD75
Capacity	(kg)	150	300	500	750	1000	700
Table Size	LxW (mm)	700x450	815x500	815x500	1000x510	1000x510	1220x610
Table Size(Euro Type)	LxW (mm)	700x450	850x500	850x500	1000x510	1016x510	910x500
Table Height	Min. (mm)	220	285/340	285/340	420	380	355
Table Height	Max. (mm)	720	880	880	990	990	1300
Handle Height	h (mm)	950	990	990	990	980	1015
Handle Type	h (mm)	Foldable	Foldable	Foldable	Fixed	Fixed	Fixed
Wheel Dia.	(mm)	Φ100	Φ125	Φ125	Φ150	Φ150	Φ125
Foot Pedal to Max. Height		≤28	≤27	≤27	≤45	≤82	≤53
Net Weight	(kg)	49	77	81	125	140	195

## Hydraulic tilt Work Table

- ▲ Reduces strain-positions your work at the precise height and angle you select.
- ▲ Choose table height range 510-700mm or 720-1070mm great for dies, mould, parts bin, etc.
- ▲ Lightweight, mobile, all-steel construction.
- ▲ Platform can be set at various heights and tilted to a certain angle to reduce strain and overexertion.
- ▲ Telescoping shaft with safety lever secures the work positioners to the height you want.
- ▲ Four swivel casters making the work positioners extremely easy to maneuver.
- ▲ Angle of table is adjustable from 0-40°.
- ▲ A valve core for pneumatic purpose.



Article No.	XL15A	XL15B	XL15C	
Capacity	(kg)	150	150	150
Table Size	(mm)		510x410	
Table Height Range	(mm)	510-700	720-1070	720-970
Adjustable Table Angle		0-40°	0-40°	0°
Net Weight	(kg)	28	30	23

## Hydraulic tilt Work Table

- ▲ Reduces strain-positions your work at the precise height and angle you select.
- ▲ Table height 720-1070mm great for dies, mould, parts bin, etc.
- ▲ Lightweight, mobile, all-steel construction.
- ▲ Platform can be set at various heights and tilted to a certain angle to reduce strain and overexertion.
- ▲ Hydraulic pump lift the platform to the height you want.
- ▲ Four swivel casters making the work positioners extremely easy to maneuver.



Article No.	XH15	XH20	
Capacity	(kg)	150	200
Table Size	(mm)		510x410
Table Height Range	(mm)		720-1070
Adjustable Table Angle			0-40°
Net Weight	(kg)	38	42